

F-Class Target Rifle (F-TR)

Match Dates: April 22nd, June 30th, July 29th

The match is "not NRA approved or registered"

Match Director: Mike Godman

Ph# 563-349-1376

Entry Fee: \$15.00

Registration time ends 8 am, squading 8:30, match start time 9:00 am. (Note: Range will be closed for set up at 6:30 am for match)

Limited to 30 shooters

Membership not required

The purpose for these matches is to introduce individuals to F-Class procedures and the way matches are ran in case they want to participate in a Mid-Range NRA approved 600 yd. match. Which in 2018- 2 matches are held at Milan Gun Club and Iowa 2 matches in Van Meter, IA (spring and Fall State shoots) and La Crosse, WI. 3 matches are scheduled.

All firearms that are out of the cases "ARE REQUIRED" to have EIC (Empty Chamber Indicator) in at all times. The only time it is to be removed is when instructed to do so when on the firing line. When Pit Changes occur and people are moving up and down range no firearms are to be handled at any time even behind the firing line until range is cleared and instructed to do so.

This is a single load only match (So AR's must have an empty mag or a Bob Sled in them to lock the bolt carrier back in position after each shot.

3 target match all at 200 yds. 2 sighters, 20 rounds for record in 22 min.

NRA MR-31 Target - X-Ring .75, 10 Ring 1.75", 9 Ring 2.75", 8 Ring 3.75", 7 ring 5.57", 6 Ring 7.75", 5 Ring 9.75".

Following F-Class Rifle Rules on equipment and rests 3.4 (b) 3.4.1 (b)

A rifle restricted to the chambers of unmodified .308 Winchester/7.62mm NATO or unmodified .223 Remington/5.56 x 45 NATO cartridge cases. The rifle must be fired off a bipod, rigidly attached to the rifle's fore-end, and or a sling. Any bipod meeting the definition of a bipod may be used but its weight must be included in the rifle's overall weight. Any safe, manual operated trigger is permitted. Any sighting system is permitted, but it must be included in the rifle's overall weight.

The rifle's overall weight, including all attachments such as sights, sling and bipod, must not exceed 18.18 pounds. An "attachment" also includes any external object, other than the competitor and apparel, which recoils or partially recoils with the rifle, or which is clamped, held, or joined in any way to the rifle for each shot, or which even slightly raises with the lifting of the rifle from its rest/firing point.

The rifle must be fired in the prone position from the shoulder of the competitor using rifle as defined.

F-Class Target Rifle (F-TR) Rests - A bipod and/or sling are the only allowed front supports for the F-TR rifle. The rifle may be supported by a bipod and/or sling and a rear support which provide no positive mechanical method for returning it to its precise point of aim for the prior shot. Subject to:

(1) The bipod and/or sling and rear support may not be attached to each other.

(2) The use of any form of a table is prohibited. Separate flat boards or plates not exceeding the dimensions of the individual rests by two inches are allowed to be placed under the front and/or rear rests. In the case of a bipod, the board or plate may not exceed the width of the bipod by 2", nor be more than 12" front to rear.

No leveling screws or provisions are allowed on these boards or plates. They must be flat on the top and bottom.

A bipod is a device with no more than two legs that touch the firing point. It must be rigidly attached to the forend of the rifle. The bipod may have rigid or folding legs, and may be adjustable to compensate for the uneven surface of the firing point.

No portion of the rifle's butt or forend shall rest directly on the ground or any hard surface. A rear rabbit eared bag, small sandbag or a gloved hand may be used to support the rifle's butt. Any rear support employed shall not be attached, clamped or held to the rifle in any manner. The rear support may not be fixed to or protrude into the firing point. Mechanically adjustable rear support is not allowed.

Any number of objects may be placed beneath the bipod or rear support, to compensate for variations in height slope of the firing point.

The bipod and or rear rest may be adjusted after any shot to compensate for the rest movement or settling. A sling may be used in conjunction with the rest (s), but its weight will be included in the rifle's overall weight.

Recommended Equipment: Shooting mat, folding chair of some sort, spotting scope and stand, rear bag (rest), confirmed zero (200 yds.), semi auto AR's use of a Sled. Original bobsled.com or empty magazine.